

Floor Bond™ XMS Hybrid Polymer Flooring Adhesive

Floor Bond XMS is a high strength, high performance, hybrid polymer flooring adhesive designed to provide a permanently flexible bond for all timber based flooring products. Floor Bond XMS provides a non-hazardous alternative to traditional polyurethane timber flooring adhesives being free from solvents and isocyanate. Floor Bond XMS contains no water therefore the adhesive exhibits no shrinkage during curing and the risk of deforming timber flooring is eliminated.



Key Benefits







- ✓ Permanently flexible
- ✓ Non-hazardous – contains no solvents or isocyanates
- ✓ Long open/working time
- ✓ Smooth and easy to trowel
- ✓ Excellent non-slump properties - forms stable peaks once applied with a notched trowel
- ✓ Acoustic rated in conjunction with matting; CSIRO Report No. INR 157
- ✓ Will not bubble when curing
- ✓ Cleans easily from the surface of pre-finished engineered boards without changing the gloss level of the pre-finish

Uses

- ✓ Bonding many types of overlay timber flooring e.g. solid, pre-finished engineered and block parquetry
- ✓ Bonding timber and cement based sub-floor products over both timber and steel joists
- ✓ Installing floors with under floor heating
- ✓ Multi-purpose full contact bonding of floor and wall lining products where a solvent free adhesive is required



Specifications
Cured State Elastomeric - flexible
Skin Time 60 - 80 mins (23°C, 50% RH)
Cure Time 3 - 4mm/day (23°C, 50% RH)
Hardness Shore A. 50
VOC 24g/L
Area Interior/exterior
Product Chemistry Hybrid polymer
Refer to TDS for additional technical information

Available Products	Colour	Ctn Qty
 960g Sausage Resource Code: 15019412	 brown	15
 16kg Pail Resource Code: 15019410	 brown	1
<p>Floor Bond XMS Sub-Floor is a high performance, sub-flooring and construction adhesive designed for bonding both timber and cement based flooring products to either timber or steel joists.</p> <ul style="list-style-type: none"> ✓ Suitable for bonding timber sub-floor to both timber and steel joists ✓ Bonding cement based wet area sub-floor products ✓ Accommodates movement in the floor, reducing the occurrence of creaking 		
 470g Cartridge Resource Code: 15019411	 brown	12

Compatible Substrates
✓ Steel inc. stainless
✓ Aluminium
✓ Metal
✓ Concrete
✓ Fibre cement sheeting
✓ Brick
✓ Plywood
✓ Particleboard
✓ MDF
✓ Timber
✓ Ceramic
✓ Plasterboard